



VMG8623-T50B Family Series

The Zyxel VMG8623-T50B Family Series provides high-speed Internet access to meet the worldwide market requirements for triple-play services. Featuring the built-in 2x2 802.11ac WLAN function that relieves troublesome wirings, this model offers extreme coverage for great WiFi user experience. Moreover, the user-oriented design allows this model to meet every customer's own style while providing powerful and practical functions.

Benefits

Ultra speed for UHD 4kTV service

The Zyxel VMG8623-T50B Family Series supports broadband access performance, which further enables operators to offer better UHD 4k IPTV services.

The triple-play powerhouse

The Zyxel VMG8623-T50B Family Series is built with sophisticated QoS and multicast traffic shaping features like IGMP v1/2/3 snooping and VLAN capabilities for premium video delivery services. To wireless IPTV operators, its built-in 2x2, 802.11ac chip is the top choice.



AC1200, dual-band WiFi with 867 Mbps* 802.11ac 2x2 Wave 2 technology



TR-069 remote management (Data model: TR-098/TR-181)



USB 2.0 high throughput for file sharing



Excellent routing and QoS capability to prioritize applications as needed



NAT, firewall with SPI and DoS for better security



Stand-alone and wall mountable



Supports VoIP SIP protocol with 3-way conference calls**



VDSL2 supports super vectoring up to profile 35b***

Carrier-class WiFi for seamless mobility

Rated as AC1200, the Zyxel VMG8623-T50B Family Series delivers speeds of up to 867 Mbps* over 5 GHz and 300 Mbps* over 2.4 GHz. For better user experience, four models offer dual-band, d WiFi with performance-boosting features such as Multi-User MIMO (MU-MIMO) and Beamforming for simultaneous, lag-free streaming and gaming experiences. In addition, its ability to create multiple WiFi networks with up to 4 SSIDs helps operators to easily create individual WLAN networks for video, data and guests.

TR-069 remote management with TR-181 issue-2 support

The Zyxel VMG8623-T50B Family Series supports TR-69 that simplifies remote configuration, upgrade and management and therefore improves cost effectiveness and customer satisfaction. Additional support to the latest TR-181 issue-2 data model also enhances service providers' visibility on subscriber LAN networks for improved customer assistance.

Specifications

System Specifications

Wireless Standard

- 802.11 b/g/n/ac 2.4 GHz, data rate 300 Mbps
- 802.11 a/n/ac 5 GHz, data rate 867 Mbps

Router/Bridge Features

- IEEE 802.1D transparent bridge & basic spanning tree
- PPPoE (RFC 2516)
- PPPoA (RFC 2364)
- MAC encapsulation routing/IPoE
- Network Address Translation (NAT)
- NAT virtual server (port forwarding)
- DHCP client/server/relay with DHCP option 43/60/61/125
- DNS proxy/dynamic DNS
- Static/Policy route
- IGMP v1, v2, v3
- IPv4/IPv6

Wireless

- Wireless Protected Setup (WPS)
- WMM
- WPA2/WPA2-PSK with TKIP & AES
- Security type
- Multi SSID: up to 4
- MU-MIMO support

VLAN/QoS

- 802.1Q VLAN tagging/un-tagging
- Support flexible traffic classification

Firewall & Security

- Generic packet filter
- DoS attack prevention
- Parental control

USB

- File sharing
- 3G back up with external 3G USB dongle

Management

- Web/HTTP: 3 level log-in via SSH or Telnet
- Firmware upgrade via web/TFTP/FTP/TR-069 RPC method
- Text based configuration
- Configuration backup/update/restore default via Web
- Configurable access control for remote management (interface and port number)
- DSL forum TR-069, TR-098***
- TR-111 and TR-181 i2
- SNMP v1, v2
- Rom-D support
- UPnP port forwarding rules on page

VoIP**

- Section Initiating Protocol (SIP), RFC 3261
- Codec: G.711 a/μ (64K), G.726 (24/32K), G.722
- G.168 echo cancellation
- Fax/modem detection and pass-through
- Voice Active Detector (VAD)
- Comfort Noise Generator (CNG)
- Dynamic jitter buffer
- DTMF detection and generation
- DTMF relay by in-band and out-of-band (RFC 2833, SIP Info)
- SIP account (URL type included)
- On hook, off hook and flash detection
- Caller ID
- Call forwarding (No condition, busy, no answer)
- Call transferring
- Call hold/Call retrieve
- Three way conference
- Call waiting
- DNS SRV

VDSL***

- G.993.1 VDSL
- G.993.2 VDSL2, Band 997, 998, Over POTS
- Support VDSL profiles: 8a/b/c/d, 12a/b, 17a, and 35b
- G.vector

ADSL***

- G.992.1 (G.dmt)
- G.992.2 (G.lite)
- ANSI T1.413 compliant
- G.992.3 (ADSL2)
- G.992.5 (ADSL2+)
- G.INP support

Hardware Specifications

- WAN: one 10/100/1000 Mbps
- Ethernet port RJ-45
- Wireless:
 - Two internal antennas (2.4 GHz)
 - Two internal antennas (5 GHz)

Interface Description

- Ethernet: four 10/100/1000 Mbps
- Ethernet ports RJ-45 (8P8C)
- USB: one USB 2.0 host
- FXS: two RJ-11 **
- DSL: one RJ-11 ***

Button

- One Power on/off button
- One reset button
- One WPS on/off button
- One WLAN on/off button

Status LEDs Indicators:

- Power/System
- WAN
- Internet
- LAN
- WLAN-2.4G/WPS
- WLAN-5G/WPS
- Phone**

Power Consumption

- 12 V DC/ 1.5 A

Environmental Specifications

Temperature:

- Operating: 0°C to 40°C
- Storage: -30°C to 70°C

Humidity:

- Operating humidity: 10 to 90% RH (Non-condensing)
- Storage humidity: 10 to 95% RH (Non-condensing)

Physical Specifications

- Item dimensions : 220 x 153 x 35 mm (8.66" x 6.02" x 1.38")
- Item weight : 325 g (0.67 lb.)

Certification

- Safety: CE-LVD
- EMC: CE

Package Content

- Wireless IAD
- Power adapter
- Ethernet cable
- Quick start guide
- Safety warning card

* The maximum wireless data is derived from IEEE Standard 802.11 specifications. Actual data transfer rate will vary from network environment including: distance, network traffic, building site materials/construction, interference from other wireless devices, and other adverse conditions.


** Supported only by VMG8623-T50B & EMG5523-T50B


*** Supported only by VMG3625-T50B & VMG8623-T50B

**** The types and number of ports and LED indicators could be changed regarding to the spec and model.

Applications Diagram

VMG8623-T50B/VMG3625-T50B





VMG8623-T50B family series


Model	VDSL2 35b Gateway		Ethernet Gateway	
	VMG8623-T50B	VMG3625-T50B	EMG5523-T50B	EMG3525-T50B
Rear Panel				
VDSL2 WAN	17a/35b	17a/35b	-	-
Vectoring/G.INP	Yes/Yes	Yes/Yes	-	-
Ethernet WAN/LAN	1 x GbE/4 x GbE	1 x GbE/4 x GbE	1 x GbE/4 x GbE	1 x GbE/4 x GbE
Wireless 2.4 GHz	2x2 11n, 300 Mbps	2x2 11n, 300 Mbps	2x2 11n, 300 Mbps	2x2 11n, 300 Mbps
Wireless 5 GHz	2x2 11ac, 867 Mbps	2x2 11ac, 867 Mbps	2x2 11ac, 867 Mbps	2x2 11ac, 867 Mbps
VoIP Interfaces	2 x FXS	-	2 x FXS	-
USB Interface	1 x USB 2.0	1 x USB 2.0	1 x USB 2.0	1 x USB 2.0
OPAL SW	Yes	Yes	Yes	Yes

Interface description

Front Panel****



Rear Panel****



ZYXEL

Your Networking Ally

For more product information, visit us on the web at www.zyxel.com

Copyright © 2019 Zyxel Communications Corp. All rights reserved. Zyxel, Zyxel logo are registered trademarks of Zyxel Communications Corp. All other brands, product names, or trademarks mentioned are the property of their respective owners. All specifications are subject to change without notice.

Datasheet [VMG8623-T50B Family Series](#)

